



GENERAL DRAWING NOTES: U.O.S.

- BREAK ALL CORNERS 0.030 RADIUS OR CHAMFER
- MACHINE ALL FILLETS 0.030 RADIUS
- ALL DIAMETERS CONCENTRIC $\pm .005$ TIR
- TURNED SURFACE FINISHES 63 RMS OR BETTER
- DRILLED OR BROACHED DETAILS 125 RMS OR BETTER
- DIM AND TOL SHALL BE HELD AFTER PLATING
- STAMP PART & WORK NUMBERS AS SHOWN
- DO NOT USE DRAWING IF MANF. HOLD IS INITIALED

REVISION HISTORY - (MOST CURRENT REV. AT TOP)

REV	DATE	INIT.	NOTES
1	3/25/04	MES	REVISION AT MOVE

TOLERANCES: UNLESS OTHERWISE SPECIFIED

- X.XX = ± 0.010 [X.XX] = ± 0.05
- X.XXX = ± 0.005 [X.X] = ± 0.1
- ANGLES = ± 1.0 DEG. [X] = ± 0.3

SCALE: NONE MATERIAL: HOFFMAN A1614NF STEEL ENCLOSURE

Do Not Scale Drawing

SCHMITT INDUSTRIES, INC. (SMS)
 2765 NW NICOLAI ST., PORTLAND, OR 97210
 TEL: (503) 227-7908 FAX: (503) 223-1258

PART: LINE SCANNER ENCLOSURE W/ FAN

NUMBER:	FILE:	SHEET:
MEN377701	MEN377701.ipt	1 / 1
DATE:	DRAWN BY:	MANF. HOLD:
3/25/04	MES	
DATE:	MANF. HOLD:	HOLD DATE: